WINC[™] Inclination Tool – The Latest in Technology

Completely digital and designed with the user in mind, our WINC positive pulse tools provide inclination and survey qualifiers, in real time. The 'Pumps-On Survey'[™] is automatic on every connection; no waiting and continue drilling.

WINC Tool (Unmanned Survey Tool)

- · Retrievable, reseatable, mud pulse tool
- Can be supplied in a pre-loaded short drill collar, in sizes: 4.75", 6.5", 8.0", 9.0", 9.5"
- · Operating battery life expectancy of 1,000 hours/40 days
- · Length is approximately 12 feet
- + Inclination accuracy, $\pm 0.10^\circ$ up to 22.5°
- Extreme LCM tolerance; over 100 lbs/barrel
- · Integrated rubber fin centralizer
- Operating temperature, 0°-150° C or 32°- 302° F
- Vibration random 20 g RMS, 15-500 Hz
- Shock 1000 g, 0.5 ms, half-sine
- · Memory shock and vibration real time
- Rated to 20,000 psi

Wireless Display

- Remote access
- Wireless LAN
- Resistive touch screen
- 10.4" rugged LED back-lit display, sunlight reliable
- High environmental performance and reliability
- Doghouse certified when 100-240 VAC, 50-60 Hz, Class 1 / Division 2, ATEX Zone 2, CE, Certified
- Optional smart phone display 'App' available
- Interface with EDR/also auto-recognition
- Auto depth capture with EDR hook-up
- · Configurable to automatically email survey reports
- · Depth tracking available

Mudlink[™] – The Decoder

- Automatically decodes and displays to tablet: inclination, temperature and battery voltage
- Two minute survey
- · Wireless communications to tablet
- Printing of survey logs
- Dual decoder available

Additional Advantages Include

- · Reduce rig time, automatic surveys on connection
- Cost and time saving alternative to single shot surveys
- Less costly than full MWD
- · Used and operated by rig personnel
- Provides fast and accurate well-bore inclination
- Simple, reliable and easy to use
- Minimizes non-drilling time, lessens chances of getting stuck, provides greater well control



WINC+ Inclination & Azimuth Tool

Winc+ (has the ability to provide inclination, azimuth and toolface, so you can keep your hole straight and on target, avoiding costly doglegging and potential hole conditions as a result of not circulating while surveying. Users call it exceptional!

The WINC+ tool is capable of surveying at any point by simply stopping the pumps and restarting them. A survey is reported back to surface while you are drilling ahead, there is no need to wait for the survey to be pumped up; it's done! When used with a steerable assembly, the WINC+ can get you back on target immediately.

Pumps ON CON CON CON CON CON CON CON	ON AZM: 95.82."	VERTER	Nig rante Well Name
Off: 00.00.22	Off: 00.00.22	ON	
562 (Center Bit Depth)	562 (Billion Bill Darph)		Walter Balling - Tables - Head
		562	Enter Bit Depth
			Mending Televis



The WINC+ System (Unmanned Survey Tool)

- Retrievable and reseatable.
- 175° C / 347° F operation.
- · Simple configuration required, easy one step, high side offset if TF needed.
- Inclination accuracy ± .10°
- Azimuth accuracy ± 0.5°
- Reliable, high LCM tolerant mud pulse technology.
- Real-time shock, vibration, temperature and RPM measurements.
- Detailed shock and vibration reports from tool memory.
- Operating battery life expectancy of 400 hours/per battery and 300 hours/per battery high speed with option to run two batteries.
- Remote log-in support and troubleshooting as well as 24/7 phone support.
- Supports ERD interface.
- · Real time RPM.
- Depth tracking option available.

User friendly; allows remote viewing from a computer or smart-phone.

Software Features

· Easy to use, minimal configuration required

Survey history stored automatically by job

Automatically email surveys from the tablet

Cost effective solution for monitoring or correcting

No need for end of well gyro costs

on the surface hole sections



VER

Western Hemisphere Sales: Quentin Paré ph +1.403.620.7273 email: qpare@vertexdownhole.com Eastern Hemisphere Sales: Jeremy Lorenowicz ph + 971.50.811.6181 email: jlorenowicz@vertexdownhole.com